

Specifications

(EVT-4000e)

BRAND		EVT		Frame		UNDER BONE				
MODEL		EVT-4000e		TXS		DIRECT DRIVEN				
DIMENSION	LENGTH		169.2cm		GEAR RATIO		DIRECT DRIVEN			
	WIDTH		64.7cm		TYPE		SEALED LEAD ACID			
	HEIGHT		101.0cm		DIMENSION (mm)		210(L) X165 (W) X175 (H)			
	AXLE LENGTH		124.0cm		WEIGHT		15.0Kg x 4			
WEIGHT	UNLOAD	FRONT	45.0Kg		SUSPE NSION	VOLUME		12V/50AH x 4		
		REAR	82.0Kg			FRONT		HYDRAULIC SHOCK ABSORBER		
		TOTAL	127.0Kg			REAR		HYDRAULIC SHOCK ABSORBER		
	RIDERS/WEIGHT		2P(150.0Kg)		TIRE		FRONT		30PSI	
SPEC	MAX.SPEED		E/35Km/hr P/45Km/hr		PRESSURE		REAR		36PSI	
	CLIMBING		10.0km/hr@14° Slope/lp		TIRE SIZE & PAIRS (p.r)		FRONT		3.00-10,6pr	
			24.5km/hr@8° Slope/lp				REAR		3.00-10,6pr	
MOTOR	TYPE		48V BRUSHED		BRAKE		FRONT		DISK BRAKE	
	CONTROLLER		PWM				REAR		DISK BRAKE	
	MAX.H.P		3.06Hp/230rpm		SPEEDO METER				80 km/hr	
		MAX.R.P.M.		700rpm						
CHARGER	CHARGING TIME		6 hr (up to 90%)		LAMPS		FRONT (HI, LO)		HI 12V/35W LO 12V/35W	
	POWER		400W				PLATE LAMP		12V/5W	
	INPUT		AC110V/220V				BRAKE LAMP		12V/21W	
	OUTPUT		48V				DIRECTION LAMP		12V/10W x4	